


GEARENCH®

TITAN HYDRAULIC FLANGE SPREADERS



- *Lightweight*
- *Fast and easy to use*
- *Jaw widths adjustable from 2-3/4" to 8-1/2" covering a wide range of flanges*
- *Available in 5 and 10 ton force capacity*

CATALOG NO.	STUD SIZE	SPREAD		CAPACITY	WEIGHT	MAX. OPERATING PRESSURE
		MIN.	MAX.			
NH56	.75" - 1.13"	2.75"	6.10"	5 tons	10-1/2 lbs.	10,000 PSI
NH109	1.25" - 1.63"	4.10"	8.50"	10 tons	24-1/4 lbs.	10,000 PSI

POWER OPTIONS

CATALOG

NO.

INCLUDES:

UHCH-P16

Hand Pump, Hose, Gauge

UHCH-P19

Pneumatic Pump, Hose, Gauge

ASA Rating (psi)	Pipe Size (in)	
	NH56	NH109
150	5 - 20	22 - 42
300	2.50 - 14	16 - 28
400	2.50 - 12	14 - 24
500	2.50 - 10	12 - 20
900	.50 - 6	8 - 16
1500	.50 - 3.50	4 - 8
2500	.50 - 2.50	3 - 4



P.O. Box 192 • 4450 South Highway 6
 Clifton, Texas 76634 U.S.A • www.gearench.com
 (254)675-8651 • fax (254)675-6100
sales@gearench.com

